PART OF ACCURAMED
MML | Medical
Your strategic partner in medical devices

# Nike Brazen Lead Glasses

**BRAZEN-02**
Matte Black / Military Blue

**BRAZEN-04**
Shiny Black

Lens Width: 60mm

Bridge Width: 16mm

Frame Width: 135mm

Lens Height: 40mm

The Nike Brazen glasses combine streamlined style, comfort and lightweight durability. They feature a nylon frame and ventilated nose bridge.

| | |
|---|---|
| **FRAME SIZE:** | 40mm - 16mm - 135mm<br>Universal |
| **WEIGHT:** | 77 G |
| **PRESCRIPTION:** | Single Vision, Plano |
| **COLORS:** | Matte Black/Military Blue, Shiny Black |
| **PROTECTION:** | .75mm LE |
| **INCLUDES:** | Anti-fog spray, safety strap add-on, protective case |

# LEAD GLASSES

# Maxx 30

**830250** Black

**830251** Red

**830252** Silver

**800070** Blue

*Optional*
Side Protection

- Prescription compatible (for most Rx)
- First protective eyewear to receive the American Ophthalmology Associations seal of acceptance.
- Meets ANSI Z87.1+ standards along with ASTM F803 impact resistance standards.
- Temple bars and nose bridge have soft rubberized padding for extra comfort
- Lightweight and comfortable
- Large lens area for maximum protection
- Bifocal Progressive Rx frame (requires segment height)

Lens Width: 53mm

Bridge Width: 17mm

Temple Length: 130mm

Lens Height: 35mm

Frame Width: 128mm

| | |
|---|---|
| **Frame Size** | Universal |
| **Prescription** | Plano<br>Single Vision (-SV)<br>Bifocal (-BF)<br>Bifocal Progressive (-BF-P) |
| **Colors** | Black, Red, Silver, Blue |
| **Weight** | 63G |
| **Protection** | .75 mm LE |
| **Includes** | Anti-fog spray, safety strap add-on, protective case |

# BR126

*BR126 X-ray protective glasses*
*(image showing the sandstone/orange design)*

*BR126 X-ray protective glasses*
*(image showing the cocoa/light blue design)*

## BR126

*X-ray protective glasses with side radiation protection zones adjacent to the front lenses*

| **Model** | **BR126** | **BR126** |
|---|---|---|
| Colour design | Sandstone/orange | Cocoa/light blue |
| Sizes | "Small-medium" and "large" | "Small-medium" and "large" |
| Lead equivalent value – front protection (50–150 kV) | Pb 0.75 mm | Pb 0.75 mm |
| Lead equivalent value – side protection (50–150 kV) | Pb 0.50 mm | Pb 0.50 mm |
| Weight | Approx. 85 g (Pb 0.75 mm) | Approx. 85 g (Pb 0.75 mm) |
| Anti-reflective coating | ✓ | ✓ |
| Glasses strap | ✓ | ✓ |
| Cleaning / disinfection | ✓ / ✓ | ✓ / ✓ |
| Conformity: DIN EN 61331-1:2016 / DIN EN 61331-3:2016 | ✓ / ✓ | ✓ / ✓ |

*Width of glasses*

140 mm (S/M)
145 mm (L)

*Height of glasses / width of glasses*

36 mm / 55 mm (S/M)
36 mm / 58 mm (L)

*Bridge width*

15 mm (S/M)
16 mm (L)

*Temple length*

130 mm (S/M)
130 mm (L)

| **MAVIG - Article Numbers** | **BR126** Sandstone/Orange | | **BR126** Cocoa/Light Blue | |
|---|---|---|---|---|
| small-medium / Pb 0.75 mm | Plano: | BR126SM7S-arc | Plano: | BR126SM7C-arc |
| small-medium / Pb 0.75 mm | Single: | BR126SM7S-arc-presc-S | Single: | BR126SM7C-arc-presc-S |
| small-medium / Pb 0.75 mm | Bifocal: | BR126SM7S-arc-presc-B | Bifocal: | BR126SM7C-arc-presc-B |
| small-medium / Pb 0.75 mm | Progressive: | BR126SM7S-arc-presc-P | Progressive: | BR126SM7C-arc-presc-P |
| large / Pb 0.75 mm | Plano: | BR126L7S-arc | Plano: | BR126L7C-arc |
| large / Pb 0.75 mm | Single: | BR126L7S-arc-presc-S | Single: | BR126L7C-arc-presc-S |
| large / Pb 0.75 mm | Bifocal: | BR126L7S-arc-presc-B | Bifocal: | BR126L7C-arc-presc-B |
| large / Pb 0.75 mm | Progressive: | BR126L7S-arc-presc-P | Progressive: | BR126L7C-arc-presc-P |